

PROBLEM TO BE SOLVED: To provide a receiver, in which the risk for sending a large quantity of busy data or audio data to a data communication network such as the Internet is reduced. SOLUTION: Concerning a terminal adapter un der communication connection with a call originating side via the Internet, when incoming request data expressing an incoming request are received from a call-originating side (S102), audio packets expressing ring back tones are succ essively transmitted to a call-originating side (S105). At this time, the number of packets to be transmitted is limited on the basis of the number of packets received from the call- originating side.

COPYRIGHT: (C)2001,JPO 국가 JP (Japan) 공개번호 2001-345803 (2001.12.14) 현재진행상태 보기 JP 문서보기 문헌종류 A (Unexamined Publication) 문헌정보보기 출원번호 2000-168206 (2000.06.05) 발명자 **OTA MASATAKA** FUJIKAWA KENJI NAKANISHI YASUAKI 촕원인 WORLD AXLE KK OI ELECTRIC CO LTD 국제쁙하분류(I H04L-012/02, H04L-012/56, H04M-003/00, H04M-011/00 PC)) FI H04M-003/00 B; H04M-011/00 302; H04L-011/02 Z; H04L-011/20 102 A F-Term 5K030: GA13 GA15 HA08 HB01 HC01 JA03 JT01 5K051: CC02 DD13 HH27 JJ13 5K101: LL02 SS06 SS08 UU15 테마코드 5K030; 5K051; 5K101 WIPS 째잎리 패밀리정보 보기